MC Analyze - 20200716150700

This page was moved to MC 11.0 - Database Release Notes Click in the link above if you are not automatically redirected in 10 seconds.

This component release is part of MarvelClient 11.0

NEW	The pre-existing, but not enabled by default, functionality of PostProcessing Analyze content is now generally available and has been improved significantly.			
	If you would like to use	e it, enable execution of PostProcessing via the Audit agent via Administration\Audit Configuration		
		MarvelClient Analyze Run additional Agents		
	Cleanup?	Run Cleanup Agent after Audit Agent has finished		
	Post Processing?	Run Post Processing after Cleanup Agent has finished		
	Alternatively, you can	also select any number of documents in the Users* views and run Actions\Y. Postprocessing.		
	The new Postprocess	ng feature will be further enhanced in future releases.		

NEW	Added several new views for PostProcessing:				
	□ Insights from PostProc.				
	·····Desktop Catalog Sync.				
	🖻 Local Databases				
	by Filename				
	by ODS Distance				
	by NTF Master				
	by BuildVer & File				
	by File & BuildVer				
	Desktop Catalog Sync.				
	This new view is synchronized with your database catalog (catalog.nsf on the same server as the Analyze database where the audit agent runs, or when run via client, on that user's mailserver).				
	It shows which icons on end users' desktops were:				
	 found in the catalog 				
	 found in the catalog but only on different servers not found in catalog but other databases for the same server were still found not found in catalog and not a single other databases was found for the same server 				
	NOTE: You need a replicated domain catalog. If you would like to use this functionality but need us to support a different setup, please				
	contact panagenda support.				
	Local Databases\by Filename				
	This new view has the following toplevel categories:				
	 duplicate replica ids on clients 				
	 o duplicate mail files with same replica id on clients o non-duplicate/unique mail replicas 				
	 onon-duplicate/databases which are a replica from a serverside database according to the catalog onon-duplicate/unique databases 				
	Local Databases\by ODS Distance				
	This new view shows how much older the ODS of each local database is compared to the user's Notes release:				
	 10 critical (system) = names.nsf (local personal addressbook) for which the ODS does not exactly match that of the Notes release (leading to stability issues and Domino policies not working) 				
	• 15 critical = any local database for which the ODS is newer than the Notes release of the user (meaning that the user cannot				
	open the database) 20 warning (system) = log.nsf, bookmark.nsf, cache.ndk and the users desktop file (file depends on Notes release), for any 				
	 ODS distance > 2 25 warning = local databases for any ODS distance > 2 - the higher the number the greater the delta between Notes release and 				
	ODS 30 bad (system) = same as "warning (system)" above, but for an ODS distance of 1 or 2 				
	 35 bad = same as "warning" above, but for an ODS distance of 1 or 2 				
	 good = local databases for which the ODS corresponds to the Notes release 				
	Local Databases\by NTF Inheritance, \by BuildVer & File, and\by File & BuildVer				
	These new views will show information about the templates used by local databases, including:				
	 whether the databases have relative, absolute, or network paths which template is being used by a given database (if any) whether there are duplicate templates for a given database 				
	The "BuildVer" views have categories that display the notes:version_number to understand whether local databases are based on older template versions.				

 Unfortunately, not all locally created databases like names.nsf and similar have this information ...

 NEW
 Added a form to better visualize Mail Archive settings collected by the optional "X. Addon Collect Mail Archive Details" agent.

FIX / ENHANC EMENT	The "X. Addon Collect Mail Archive Details" agent has been enhanced to also report on archive settings, even if the archive cannot be opened.	
ENHANC EMENT	ed behavior when opening a user document from any detail document (desktop, notes.ini etc.).	
	Previously it was only attempted by replica id, potentially searching for the user document in the replica on the top of the MC Analyze icon stack. Now, the Analyze database first checks whether the user document can be found by current file path, with fallback to replica id.	