

The Admin Tab

The Admin tab displays the following information and allows for the configuration of the following special settings:

The screenshot shows the 'Admin' tab of a configuration interface. At the top are four tabs: 'What', 'When', 'Who', and 'Admin', with 'Admin' being the active tab. Below the tabs, there is a 'Title:' label and a text input field. To the right of the title field is a 'Status:' label and a green button with a checkmark and the text 'Enabled'. Below the title field is a yellow highlighted area containing a Rich Text field with a small icon and a dropdown arrow. Below this is a timestamp and user information: '10.04.2008 20:30:42: Created by florian vogler/panagenda' and '07.08.2013 18:29:21: Last modified by florian vogler/panagenda'. Below this is a checkbox labeled 'Staged'. To the right of the 'Staged' checkbox is a label 'Alias(es):' followed by a text input field containing 'alias_of_this_action'. Below this is a checkbox labeled 'Run on reference only'. Below this is a label 'Execution of this action depends on the following action(s):' followed by a text input field containing 'another_action_alias' and 'yet_another_action_alias'. Below this is a label '(Optional) priority (between 2.000.000.000 and 3.999.999.999):' followed by a text input field containing '15'. Below this is a 'Remarks:' label and a text input field. Numbered callouts 1 through 7 point to various elements: 1 points to the timestamp/user info, 2 points to the 'Staged' checkbox, 3 points to the 'Alias(es):' label, 4 points to the 'Run on reference only' checkbox, 5 points to the 'Execution of this action depends on the following action(s):' label, 6 points to the '(Optional) priority' label, and 7 points to the 'Remarks:' label.



Note that the available fields on this tab differ across the various types of documents in the MarvelClient Configuration database.

1. Information about who created the document and when
Information about who last modified the document and when
2. Whether an action is staged or not - Note that this field is only visible for users with the Role [Staging] in the Access Control List (ACL) of the MarvelClient Configuration database - for further details, see Staging.
3. The alias(es) of an action - Note that not all document types allow for the configuration of an alias
4. Some actions display a checkbox "Run on reference only" on the Admin tab;
This special Runtime can either be selected on the What tab of Actions, or on the Admin tab for when there are no Runtypes to choose from on the What tab.
Any Action set to "Run on reference only" will be executed when needed (=referenced) by another Action, if it has not already been executed earlier.
See also important [Further details for Understanding Order of Execution](#).
5. Alias(es) of action(s) that this document depends on.
When specifying dependent actions, an Action is only run, if all dependent Actions are successfully executed, too.
If any action in the dependency chain fails, any other dependent Actions are not executed.
Non-matching conditions or being excluded from an Action via the Who tab both lead to an Action failing to execute.
6. The (optional) Priority of an Action
Note that every Action has a *recommended* range indicated in front of the priority input field. If you really know what you are doing, values outside of the recommended range can be used.
By default, an Action will have the priority in the exact middle of the recommended range.
7. A Rich Text field for optional remarks. Any herein entered content is also displayed on the What tab when opening a document in read mode.

Topics

- [Action Alias\(es\)](#)
- [Run on Reference Only](#)
- [Execution of this Actions Depends on the Following Action\(s\)](#)
- [\(Optionally\) Specifying the Priority for an Action](#)
- [Adding Remarks to an Action](#)