

Release Notes 2011-04-24

Config db ntf: 20110424141500
 Analyze db ntf: 20110424141500
 Windows Version: 2.0.17 :: MAC OS X Version: 1.10.14 :: Linux Version: 1.10.14
 Eclipse Plugin:

Major Improvements: New Action dependencies feature, Performance improvements, Run any clientside Notes tasks, Hide stack, Hide Replica from File-Database-Open, ID file certifier Monitoring, Basic vs. Standard client install type Monitoring, Several new views to audit local databases, Enhanced Analyze cleanup options, New Analyze Automailer feature

General Notes	
	<p>Supported IBM Lotus Notes releases: 5.x, 6.x, 7.x, 8.x, up to 8.5.2 FP2 (Administrators need at least IBM Lotus Notes 7.x on Windows or Linux)</p> <p>Supported client-side operating systems: Microsoft Windows NT4 (>=SP2), 2000, XP, 2003, 2008, Vista, 7, and Citrix/WTS, Apple Mac OS X Leopard</p> <p>Supported server-side operating systems: any supported by IBM (operating system independent)</p> <p><i>NOTE: Support is limited for platform and release combinations not supported by IBM</i></p>
	<p>Linux & Mac OS X: Skinning, Realtime, Zip/Unzip and Attachment Blocking are not available on Linux or Mac OS X; also, MarvelClient on Mac OSX a Login - Before Sync - any such actions must be set to run "After Login" (Agents and INI Management)</p>
	<p>This release contains select important updates highlighted in red</p> <p>NOTE that many of the changes/enhancements/fixes documented for config/analyze database require a DLL update - the DLL release notes which respective DLL release.</p> <p>IMPORTANT NOTE FOR customers running MarvelClient 2.0.x: This new release comes with a new action dependencies feature and <i>signifi</i> are advised to update to at least 2.0.9 in case they have an earlier 2.0.x release. Ideally, customers should update to 2.0.17 to experience all enhancements</p> <p>NOTE that release 2.0.17 also includes several enhancements for MarvelZip customers</p>
Configuration Database	
N EW	<p>Added an option to the run program action for running any clientside notes task with any paramaters, without prompting users for a passw (this new feature does NOT require "do not ask for password by other programs" checked in security settings/id file);</p> <p>includes option to wait/not wait for the respective process, plus optionally displaying a message if waiting is enabled</p> <p>Added two examples to the configuration database for running a local database ncompact and nconvert.</p>

NEW	<p>Added option "execution of this action depends on the following action(s)" to the Admin tab for the majority of all actions - here, administrators can specify must run successfully!) in order for the dependent action to run, too</p> <p>Note that dependencies overrule the general order in which actions are executed - actions are usually executed in the following order:</p> <ol style="list-style-type: none"> 1.) by runtime (e.g. Before login, after login, at shutdown) 2.) within each runtime by priority (see config database - All Actions by RT, Prio, Title for an overview on when your actions run) 3.) actions with same priority are executed alphabetically by title <p>if action A depends on actions B and C, and actions B and C have not yet been executed when action A wants to run, this will automatically trigger action B and C respectively <i>priority!</i> == actions B and C then run before action A as action A must run them to determine whether it itself should run or not.</p> <p>Note that if an action depends on another action that is not set to run within the same runtime, the depending action will fail - e.g. action A after login depends on action B, which is set to run at shutdown. In this scenario, action A cannot make action B run, since B does not have a runtime.</p> <p>Also note that all actions an action depends on must execute successfully. Executing successfully does not necessarily have to mean "run successfully" a desktop icon action to execute successfully (=meet all conditions / user restrictions to run), but the desktop icon action does not find or create a local icon, leading to the location action to run.</p> <p>(As a sidenote, the state of a local replica can be queried from within other action (or rather conditions) by <alias_of_desktop_icon_action:replica_type condition and action examples in config db for details).</p>
NEW (Windows only)	<p>Added new action "FilesJSFD. Smart File Downloader" to download large files (for e.g. client upgrades) with configurable load balancing down to client. This is available as a new module (requires a license file update). Customers who have licensed MarvelClient Professional (=Analyze+Migrate+Manage) are entitled to this module for FREE.</p> <p>The new module is called "Upgrade" and allows for seamless client upgrades from any current Notes release and install type into any target Notes release. Detailed documentation on the Smart File Downloader is available on http://kbase.panagenda.com</p> <p>Detailed documentation on how to easily upgrade Notes clients seamlessly, flexibly and above all reliably is available on http://kbase.panagenda.com</p>
NEW	<p>Added an additional option to the "AdvancedJXTX. Extended XML Export" action to export ID file details into a separate XML file:</p> <p>The resulting keyfile.xml file can be backed up into the Analyze database and reported on using two new views added therein (see Analyze database release notes)</p>
ENHANCEMENT	<p>Added several new condition examples, especially for upgrade (e.g. checking for Notes release, physical memory, free disk space, ...)</p>
ENHANCEMENT	<p>Added a "Comments" tab to location documents - this tab is not shown on end user clients, but allows for documentation of changes in a hidden "Comments" document as specified.</p>

E N H A N C E M E N T	Added a new option to the "Replication" tab in location documents to prompt/not prompt for whether a user wants to replicate during client shutdown
E N H A N C E M E N T	Added an additional five optional lines to the "Files\Backup" action
E N H A N C E M E N T	Added an additional five optional lines to the "Files\Roaming/Rollback" action
E N H A N C E M E N T	<p>Added an option to "Settings\MarvelZip\CZIP. Zip/Unzip" configuration to specify the codepage for zipped files - for international customers, the default behaviour), for Japanese and Chinese clients Unicode may be a better choice;</p> <p>NOTE that external recipients may not be able to open Unicode codepage based zip files, as not all zip/unzip utilities support Unicode.</p>
E N H A N C E M E N T	Added an option to mailbased install documents to <i>attempt</i> automatic shutdown of the Notes client (Windows only) - if there are open documents, the user can choose to continue the shutdown or cancel shutdown.
E N H A N C E M E N T	Added an option to mailbased install documents to run a program at end of install (Windows only)

FIX / CHANGE	Changed the header of the PostOpen Script calculated from mailbased install documents to document how to best integrate the script code into mail clients:
ENHANCEMENT	Added an option to Online Update to also execute a manual update by running online update from manually downloaded and unzipped files
ENHANCEMENT	Online Update now supports updating 1-n Analyze databases - simply enter one or multiple Analyze database URLs into the field - example:
CHANGE	Added further details to the message box being displayed when the config database claims that it requires an online update
FIX	Fixed a problem where rollback jobs created from the Analyze database did not contain an author field for the respective end user in the configuration in end users not being able to reset the rollback job once executed
FIX / CHANGE	<p>When opening actions in read mode, any comments entered on the Admin tab will now also display on the what tab upon document open. When switching the comments field will not display on the What tab again until the document is closed and reopened.</p> <p>Comments will naturally always display on the Admin tab as before.</p> <p>When opening actions in edit mode, comments will only be displayed on the Admin tab as has been the case previously, too.</p>
FIX	<p>Fixed various minor issues with online update - At least one of the Online Update options should now work for every customer:</p> <ol style="list-style-type: none"> 1.) LotusScript with direct connect via HTTP 1.0, HTTPS 1.0, HTTP 1.1 or HTTPS 1.1 (the protocol version typically only makes a difference when using proxies) 2.) LotusScript with proxy connect via HTTP 1.0, HTTPS 1.0, HTTP 1.1 or HTTPS 1.1 (some proxies require HTTP, other HTTPS, some version 1.0, some 1.1) 3.) Java with direct connect via HTTP 1.0, HTTPS 1.0, HTTP 1.1 or HTTPS 1.1 (the protocol version typically only makes a difference when using a proxy) 4.) Java with proxy connect via HTTP 1.0, HTTPS 1.0, HTTP 1.1 or HTTPS 1.1 (some proxies require HTTP, other HTTPS, some version 1.0, others 1.1) <p>NOTE that Java is a requirement in Asia</p> <p>5.) Manual update by downloading the update files manually and unzipping them for further "install (of a) prepared update"</p>
FIX	Fixed a problem with online update also reporting currently downloaded (==most recent) templates as duplicate
FIX	Fixed a problem where online update using Java resulted in a save conflict prompt
FIX	Fixed a problem where the postopen script generated from within mailbased install documents did not work (would not find install document in configuration)

Analyze Database	
N EW	Added a new view "Users\by Startup/Shutdown" to show when a client was last started/shutdown by whom. Note that for the view to properly display all startup/shutdown times, you must upload config.xml "after login - after write" AND "at (end of) shutdown" (l
N EW	Added a new view "Waiting for deletion" to display soft deleted documents as a result of the cleanup feature (see details further down)
N EW	Added a new "My Favorites" folder into which admins can pull user profiles they wish to later again revisit (this is a personal on first use folder)
E N H A N C E M E N T / N EW	<p>The "Lotus Notes\by Notes & MC release" view has been enhanced to display more details on basic vs. standard Notes 8 clients:</p> <p>The client type is derived from notes.ini InstallMode= If this entry is missing OR suggests that only a basic client is installed (InstallMode=0), but a client is started as standard (=Eclipse) client, it would resi Independent of notes.ini InstallMode, MarvelClient also checks for wether rcplauncher.exe exists in the [IBM Lotus Notes Program\framework\rcp] dire a standard client.</p>
E N H A N C E M E N T / N EW	Similar to above enhanced detection of basic vs. standard Notes 8 client, the detection of wether users have client only or client and/or designer and/o checking for physical designer.exe and admin.exe files in the [IBM Lotus Notes Program] directory.
E N H A N C E M E N T / N EW	<p>Added various new views for local database reporting:</p> <ul style="list-style-type: none"> + by NTF Inheritance shows which local databases inherit their design from which template + by NTF Master shows which local databases are which template + Sizes by User shows how much disk spaces clients consume through "local" databases in their Notes Data directory (be that local or on a network d + Sizes by GB shows how many databases there are in end user data directories in 0,1 GB spreadings + Sizes by Path shows how much disk space clients consume in which path + Sizes by Replica ID shows which Replicas consume how much disk space
N EW	<p>Added two new views for optional extended XML exports (and hence backups of these XML export files into the analyze database) of keyfile (==ID file</p> <ul style="list-style-type: none"> + by Act. & Expiry Date shows when ID files have been activated and when they expire + by Cert. & Issuer shows which certifier key an ID file has been issued with - this can help to detect user IDs that have been created with similar looki
FIX	Fixed a problem where clicking on "run cleanup once now" in the "Cleanup & more" option did not save the most recent changes made prior to executi last configuration from when the form was opened)

E	Cleanup has been enhanced as follows:
N	Cleanup can now be configured to also automatically delete redundant profiles by
H	a.) either notes username
A	b.) or notes username and profile key
N	
C	a.) can be helpful when upgrading from e.g. Notes 7 to Notes 8 and automatically delete all but the most recent profile for each user on an ongoing ba
E	b.) can be helpful when changing the profiling (backup) key and doing a manual cleanup once

In addition, Cleanup now also allows for soft deletions - if activated, redundant profiles AND outdated documents will then show up in above mentioned list and can be deleted for good according to the number of days entered in the respective field.

CHANGES	<p>Changed the XSLT notes_ini file to exclude any lines in notes.ini that do not express a variable=value pair (-> exclude all lines that do NOT contain an equal sign ("="))</p> <p>This significantly reduces the size of the various notes.ini views in the analyze database as soon as all users have uploaded a new profile with notes.ir</p> <p>To immediately update all documents for the notes.INI analysis improvements in ONE GO, please do the following:</p> <p>1.) in any ONE of the Notes.INI\... views, select all documents and then run "Actions\M. Reset Checksum"</p> <p>2.) Then, in the view "Users\by State & Upload Key", select all documents and run "Actions\M. Remove Updated Field <> 0"</p> <p>3.) Last, in the same view as 2.), select all documents and run the "audit selected" action (or wait for the scheduled audit agent to update the local data)</p>
ENHANCEMENTS	<p>Changed the behaviour of the "Audit selected" view action so that it will not memorize selected documents; in prior releases, after clicking on "Audit selected", thereby potentially leading to accidentally deleting documents that were selected for auditing along with newly selected documents afterwards. a clock symbol</p> <p>and unselected all selected documents, to then execute the audit in the background.</p>
ENHANCEMENTS	Added details about which Notes client is installed to the user profile form:
FIX	Fixed the problem of user profiles displaying "Windows Futurama ..." as platform details
.DLL Updates (Windows)	
NEW (2011-01-11) - Zip / Unzip	Added an option to MarvelZip configuration to support codepages other than the default OS default - see config database release notes for details
NEW (2011-01-11) - Zip / Unzip	Unicode zip files are now supported

N E W / E N H A N C E M E N T (2 .0. 1 1)	<p>Added notes:installed_admin_validated, notes:installed_designer_validated, notes:mode_installed_validated to config.</p> <p>MarvelClient now checks for whether certain files (admin.exe, designer.exe) or folders (client_dir/framework) exist for the current client install.</p>
N E W / E N H A N C E M E N T (2 .0. 1 1)	<p>Made sure that all notes:mode_xxx and notes:installed are always available (or set to string "unavailable"). Previously e.g. restricting actions using stri</p> <p>reliable, as the references could not be resolved at all.</p>
N E W / E N H A N C E M E N T (2 .0. 1 0)	<p>The action "Advanced\JXTX. Extended XML Export" has been enhanced to also allow for export of keyfile (=ID file) details into a separate keyfile.xml \</p> <p>database for auditing ID file details.</p>
N E W / F I X (2 .0. 1 /2 .0. 2)	<p>A new ECL will now be created if missing (e.g. if MarvelClient creates a new local addressbook).</p> <p>This can be disabled by setting the notes.ini-variable MC_ECLCheckCreateMissing=0</p>

N E W (2 .0. 0)	Added support for action dependencies - see config database release notes above for details.
N E W (2 .0. 0)	Added new action "Advanced\JFOR. Notes @Formula" which allows to run a Notes @Formula. The result of the formula can be used from within other via its alias.
N E W (2 .0. 0)	Added new action "Advanced\JESTR. Escape String" which allows to escape a set of characters
N E W (2 .0. 0)	Added a new option to desktop icon action to automatically add all cluster members of the primary to must-/mayhave lists
N E W (2 .0. 0)	Any changes to the current workspace page layout before synchronisation now honor the page focus accordingly
N E W (2 .0. 0) - R o a m ing	The last focussed page on the desktop/workspace is now roamed along for clients < release 8 and Notes 8 basic clients.
N E W (2 .0. 0)	Workspace page actions can now set the page focus on client startup for clients < release 8 and Notes 8 basic (=Non-Eclipse) clients. The last action actions are configured to set the focus for a particular user/client
N E W (2 .0. 0)	Added various actions and options for integration of MarvelClient with GroupExplorer Automate In short, GroupExplorer Automate allows to automatically manage all or a subset of databases on end user workspaces in sync with databases and ACL creation/deletion/moves/ACL changes/Group Changes/and more is automatically synchronized with client workspaces based on serverside changes = server to another, GroupExplorer Automate automatically synchronizes the move with client workspaces without the having to create any action manually added or removed from an ACL or a group in the public names- and addressbook (NAB), the respective databases s/he now has access to are automatically added or removed from an ACL or a group in the public names- and addressbook (NAB), the respective databases s/he no longer has access to are automatically being removed. If you are interested in further details for automating workspace configuration contact support@panagenda.com
N E W (2 .0. 0)	Added an option to desktop icon action to allow managing the "do not browse" flag in local replicas to (un)hide them from the UI (File - Open - Lotus Notes - "leave as is" option).

N E W (2 .0. 0)	Added an option to desktop icon action to hide an entire icon stack (included local icons only, too)
N E W (1 .1 0. 2 9 /3 0)	Added a new option to the Run Program action to run Notes client tasks without end user interactions (e.g. ncompact or nconvert), including an option as display a progress bar if waiting for it to finish 1.10.30: removed the MarvelZip logo from optional progress bar display
N E W (1 .1 0. 2 2)	Added a new placeholder for use of OS environment variables: Use %env_ENVIRONMENTVARIABLENAME% syntax in applicable notes.ini entries (
N E W (1 .1 0. 1 5)	Added a new boolean option mc:replpage_nocreate (default: false) which allows to specify whether MarvelClient should create an (almost) empty replicator page to false (==default), MarvelClient will create a replicator page along with newly created locations and any replicator page management actions will work. If set to true, newly created locations will not have a replicator page on first run and MarvelClient can not apply replicator page management actions in this is known to often create so called cutoff date problems (=replicate documents back to the server that have long been deleted). It is recommended you really know what you are doing.
N E W (1 .1 0. 1 3)	Added new variables mc:time_* to config which log the date/time of beforelogin, afterlogin and shutdown
N E W (1 .1 0. 1 3)	Added os:logonsessions (incoming remote sessions) to config
N E W (1 .1 0. 1 3)	Added new variable os:citrix_no_logonsessions; bool; is true when (os:citrix == 1) AND (os:logonsessions <= 0)
N E W (1 .1 0. 1 3)	The path to MarvelClient dll is now available in config as mc:addin_path, mc:addin_directory, mc:addin_filename

NEW (1 . 1 0. 9)	Added new config values for notes section: installed_admin (0/1), installed_designer (0/1), mode_installed (basic, standard, nomad_basic, nomad_sta
CHANGE / FIX (2 . 0. 0)	If newly created, the "do not browse" flag is now set for mc_localstore.nsf to hide it from File - Open - ...
CHANGE (2 . 0. 0)	Changed hidestack for unstacked desktops; now unstacked stacks will always get unhidden if hidestack is set to false (or not set at all) - after all, if an icons should not exist for it.
CHANGE / ENHANCE MENT (2 . 0. 0)	Changed merge/unmerge in config notes.ini & variables action to now compare trimmed values (leading/trailing whitespace is removed prior to checkin comparison has been improved to now being case-insensitive
ENHANCE MENT (2 . 0. 1 7)	Improved inplace editing of single file zips

E N H A N C E M E N T (2 .0. 1 7)	Added mc:last_fs_roaming_failed to config - this is "1" (otherwise==default "0") if file system roaming failed to access root folder during client startup - backup at shutdown
E N H A N C E M E N T (2 .0. 9)	Added a new feature which automatically handles configuration database replica changes - clients now memorize in actions.xml which replica ID the user is switched to a different replica, the entire actions.xml is recreated from scratch (=deleted and recreated according to all relevant actions of the n
E N H A N C E M E N T (2 .0. 8)	Opening of local databases that need a fixup can now be turned off via mc:db_checkfixup (bool, optional, defaults to false). If a database is detected to be below a size limit. mc:db_checkfixupsize limit_mb (size in MB, optional, defaults to 0 - means any db that needs fixup will not be opened if mc:db_checkfixupsize Using this variable you can e.g. prevent significantly prolonged startup times for consistency checks of large local database (e.g. mail file replicas) - prevent replica from being managed in that respective run (since, if MarvelClient is not allowed to open the database, it cannot manage it).
E N H A N C E M E N T (2 .0. 8)	Writing databases.xml will now only collect additional details from an open database if an extended xml export is used (in previous versions it has written time of writing) - this should also improve startup times noticeably

E N H A N C E M E N T (2 .0. 8)	<p>The local database scanner now ignores several directories in the Notes data directory by default (%DATA%\domino, %DATA%\workspace and %DATA%\local). Optionally, this can be controlled via mc:db_scan_excludedefaultdirs (bool, optional, defaults to true). For Eclipse clients, this should result in significantly faster client startup times as we no longer scan ~20,000 files but only a few hundred.</p> <p>In addition, scanning for local databases can now also ignore additional paths:</p> <ul style="list-style-type: none"> +) mc:db_scan_unc (bool, optional, defaults to false == <i>by default, MarvelClient will NO LONGER scan databases pointed to on the workspace/in boot</i>), and +) mc:db_scan_otherdrives (bool, optional, defaults to true), and +) mc:db_scan_datadirdrive (bool, optional, defaults to true) to control. <p>mc:db_scan_unc controls scans on paths starting with "\\ ", mc:db_scan_otherdrives controls scans on paths on drives other than the one the data directory controls scans on paths that are on the same drive as the data directory.</p> <p>Typically only Administrators have icons/bookmarks pointing to UNC paths (e.g. \\192.168.x.x\... or similar), and excluding them should not affect creation of local replicas for end users on UNC paths, you MUST explicitly enable mc:db_scan_unc!</p>
E N H A N C E M E N T (2 .0. 1)	<p>Skinning now supports resolution-specific backgrounds - if during client startup, we find a def_background_XxY.bmp (where X and Y are width/height in pixels), MarvelClient will load that background, otherwise it will fall back to def_background.bmp</p> <p>Example filename: def_background_1920x1200.bmp</p>
E N H A N C E M E N T (2 .0. 0)	<p>The desktop icon action now allows to specify a list of servers in musthave list</p>
E N H A N C E M E N T (1 .1 0. 2 4)	<p>If for - e.g. testing purposes - the config database is on local, MarvelClient will now resolve %LOOKUP_*. values for location documents from the user management would fail to resolve any such values with a config db on local)</p>

<div> <div> <div> <div> <div>E</div> <div>N</div> <div>H</div> <div>A</div> <div>N</div> <div>C</div> <div>E</div> <div>M</div> <div>E</div> <div>N</div> <div>T</div> <div>(1</div> <div>.</div> <div>1</div> <div>0.</div> <div>2</div> <div>2)</div> </div> </div> </div> </div>	<div> <div>If there is an error accessing the MC_WorkingDirectory as specified in notes.ini, MarvelClient now falls back to default working directory location</div> </div>
<div> <div> <div> <div> <div>E</div> <div>N</div> <div>H</div> <div>A</div> <div>N</div> <div>C</div> <div>E</div> <div>M</div> <div>E</div> <div>N</div> <div>T</div> <div>(1</div> <div>.</div> <div>1</div> <div>0.</div> <div>2</div> <div>2)</div> </div> </div> </div> </div>	<div> <div>Improved logging for field changes in location and connection documents</div> </div>
<div> <div> <div> <div> <div>E</div> <div>N</div> <div>H</div> <div>A</div> <div>N</div> <div>C</div> <div>E</div> <div>M</div> <div>E</div> <div>N</div> <div>T</div> <div>(1</div> <div>.</div> <div>1</div> <div>0.</div> <div>2</div> <div>0</div> <div>/2</div> <div>1)</div> </div> </div> </div> </div>	<div> <div>Enhanced fallback for config notes:homeserver - if %notes_homeserver% cannot be resolved from the current location, MarvelClient now uses ini:MailServer</div> </div>
<div> <div> <div> <div> <div>E</div> <div>N</div> <div>H</div> <div>A</div> <div>N</div> <div>C</div> <div>E</div> <div>M</div> <div>E</div> <div>N</div> <div>T</div> <div>(1</div> <div>.</div> <div>1</div> <div>0.</div> <div>1</div> <div>8)</div> <div>-</div> <div>R</div> <div>e</div> <div>a</div> <div>l</div> <div>t</div> <div>i</div> <div>m</div> <div>e</div> </div> </div> </div> </div>	<div> <div>Relocation actions now support <rel:mailserver>, <rel:mailpath>, <rel:maildirectory> and <rel:mailfile> (based on notes.ini MailServer & MailFile entries)</div> </div>

E N H A N C E M E N T (1 .1 0. 1 7) - Zi p / U n zip	Added helper text to pwd / pwd confirm fields
E N H A N C E M E N T (1 .1 0. 1 7) - Zi p / U n zip	Default value of encrypt check box can now be configured from config "Settings\MZip. ..."
E N H A N C E M E N T (1 .1 0. 1 1) - R o a m ing	Improved logging for roaming

FI X / E N H A N C E M E N T (2 .0. 1 3) - R o a m ing	MarvelClient will now no longer export/roam duplicate entries - in addition, entries with name longer than 79 bytes will not be exported/roamed, as the name is > 79 characters.
FI X (2 .0. 1 7)	Fixed broken drag & drop of encrypted zip file attachments for Notes releases >= 8.5.x
FI X (2 .0. 1 6)	MarvelClient will now properly report on the exact Windows 7 and 2008 releases (previously MC would report "Windows Futurama") NOTE: if you have conditions set to compare the windows platform with "Windows Futurama", you must change your existing conditions accordingly!
FI X (2 .0. 1 6)	Fixed a problem where for one user out of so far several 100,000 %OS_USER% could not be resolved using Windows API calls - MarvelClient now fa
FI X (2 .0. 5- 2. 0. 7)	Fixed a problem with waiting for a Notes task to finish (previously, MarvelClient would not detect wether the task is still running under all circumstance:
FI X (2 .0. 4)	If there is no desktop during client startup and MarvelClient is set to not create an empty desktop (default is autcreate if missing), MarvelClient will no
FI X (2 .0. 3)	When enforcing a path for a local replica to a new position within the data directory we used a relative path the function to check for free disk space co space" errors in log.xml and is now fixed

FIX (200)	Managed pages (=move/remove unmanaged icons option on workspace page action) now also work for unstacked desktops/workspaces
FIX (200)	Fixed Citrix detection to exclude inbound logon sessions (in previous releases, a citrix session was wrongly assumed if screen sharing was done remotely)
FIX (11025) - Process additional actions.xml files	When processing additional actions.xml files with actions that are set to "retire delete", the code for deleting an empty actions.xml (if applicable) is now fixed (and will now write an empty xml file instead)
FIX (11024) - Roaming	Fixed a problem where a roaming action would fail if ini:MC_LastProfilingKey_Conv was empty
FIX (11021)	Fixed a problem when opening notes (==documents) with OPEN_RAW_MIME flag(s) in local names- and addressbook.

FIX (1.0.1.7) - Zip/Unzip	Removed cancel button in wrong dialog (cancel could be used to skip encryption)
FIX (1.0.1.6) - ZapNotes	Added exception for new 8.5.2 preloader task (nntspred.exe)
FIX (1.0.1.3) - Roaming	Fixed a problem in backup action with zipping names.nsf on citrix
FIX (1.0.1.1) - Zip/Unzip	Fixed a wrong description for encryption option
FIX (1.0.1.0) - Zip/Unzip	Fixed Japanese translation for Zip/Unzip dialog

FI X (1 .1 0. 9) - R o a m i n g	Occasionally outdated files were roamed if the working directory contained %notes_user% placeholder. Roaming files are now deleted every time the working directory changes
FI X (1 .1 0. 9) - Z i p / U n z i p	Fixed a problem where the filename field in file save dialog in >= 8.5.1 was not grayed out when unzip flag was checked
.dylib Updates (Mac OS X)	
FI X (1 .1 0. 1 4)	Hotfix for proper handling of desktop icon urls with windows UNC paths on mac/linux
FI X (1 .1 0. 1 2)	Fixed file based roaming problems on unix platforms. Roaming now properly uses platform specific separators for filesystem operations (/ vs. \)
FI X (1 .1 0. 8)	Fixed a problem where the wait cursor would display during client startup and MarvelClient synchronisation
FI X (1 .1 0. 7)	Fixed a problem where Notes would not start when MarvelClient would attempt to open a database that required a fixup
.so Updates (Linux)	
FI X (1 .1 0. 1 4)	Hotfix for proper handling of desktop icon urls with windows UNC paths on mac/linux