

Fast start into the MC Config database



Tip: Press [F1] at any time in the MarvelClient Configuration and Analyze databases for context-sensitive help. When creating or editing documents in the MarvelClient configuration database, pressing [F9] validates your input.

The MarvelClient Configuration database is laid out as follows:

The screenshot shows the MarvelClient Configuration database interface. The interface is divided into several sections:

- 1**: A link to the MarvelClient Analyze database (top left).
- 2**: The name of the user who opened the Configuration database (top center).
- 3**: A language selector (top right).
- 4**: The Action bar (top center, below the user name).
- 5**: The Navigator to switch between views and configuration options (left sidebar).
- 6**: The currently opened view or configuration form (main content area).
- 7**: Indicator whether the database was opened on local (red) or on (which) server (green) (bottom left).
- 8**: A link to display version information about the Configuration database (bottom right).

The main content area displays a table of configuration items:

#	Active	0/1	Priority	Type	Who	When	Last modified UTC+SEQ	Conditions
27	4							
18	7							
7	0							
233	170							
4	0							
6	2							
1	0							
1	0							
2	1							
3	0							
2	1							
1	0							
1	0							
1	1							
1	1							
1	1							
1	0							
6	0							
52	6							
1	0							
8	0							
8	2							
3	0							
2	0							
3	0							
2	1							
1	0							
1	0							
2	0							

1. A link to the MarvelClient Analyze database
2. The name of the user who opened the Configuration database
3. A language selector
4. The Action bar
5. The Navigator to switch between views and configuration options
6. The currently opened view or configuration form
7. Indicator whether the database was opened on local (red) or on (which) server (green)
8. A link to display version information about the Configuration database

Topics

- [About Actions](#)

- About Conditions
- Configuration Basics - General Fields in the Header Area of Actions
 - Enabling / Disabling a Document
 - Giving a Document a Title
- The What, When, Who and Admin Tabs
 - The What Tab
 - The When Tab
 - Specifying How Often an Action Is Supposed to Run (Repeat Interval)
 - The "Keep local exec. info" Option
 - Configuring a Maximum Number of Executions
 - Selecting One or Multiple Conditions
 - Selecting One or Multiple Conditions of Which ALL Must Match for an Action to Execute
 - Selecting One or Multiple Conditions out of Which At least ONE Must Match for an Action to Execute
 - Combining the ALL and At Least ONE List of Conditions
 - Restricting an Action to Only Run for Users with a Specific Home/Mail Server
 - The Who Tab
 - Specifying Target Users for an Action (ONLY FOR)
 - Selecting Access Definitions
 - Specifying Target Users for an Action (ONLY FOR - Direct Input)
 - Excluding Users, Groups and/or Certifiers from Being Targeted by an Action
 - Excluding Users from an Action (EXCLUDE - Direct Input)
 - Under the Hood of the Who Tab
 - The Admin Tab
 - Action Alias(es)
 - Run on Reference Only
 - Execution of this Actions Depends on the Following Action(s)
 - (Optionally) Specifying the Priority for an Action
 - Adding Remarks to an Action
- About Runtypes
 - Understanding Order of Execution
- About References and Placeholders
 - References - Namespaces
 - References - the mc (MarvelClient) Namespace
 - References - the mz (MarvelZip) Namespace (Windows Only)
 - References - the notes (HCL Notes client) Namespace
 - References - the os (Operating System) Namespace
 - References - the filesystem (Operating System File System) Namespace
 - References - Syntax
 - References in References
 - Special References to Desktop Icon Actions
 - Placeholders