

Admin Interface and Config Manager


iDNA Applications 3.5.0 comes with a rebuilt admin interface. This article describes its pages and the new Config Manager, a wizard that sets up the data collection for a Domino domain in four steps.

- [Overview](#)
- [License](#)
- [User ID](#)
- [Config Manager](#)
- [Server List](#)
- [Content Packages](#)
- [What Changed for Existing Installations](#)
- [Related Topics](#)

Overview

The admin interface is where you tell iDNA what to collect and from where: the license, the Notes ID that iDNA uses to access your Domino servers, the list of Domino servers, and the content packages that define which data iDNA collects from which servers.

- **Address:** `https://<your iDNA host>/idna/config`. `https://<your iDNA host>/idna/` opens it as well, and the previous address `/idna/cfgc` redirects to it.
- **Login:** an iDNA account with the administrator role. On a new installation, log in with the default credentials (see [User Web Portal](#)) and change the password right away (see [Change Password](#)).
- **Sidebar:** the pages [License], [User ID], [Server List] and [Config Manager], followed by the content packages under [Core Config] and [Optional Config]. At the bottom, [Portal] opens the iDNA Portal and [Advanced Settings] opens iDNA's system pages, each in a new browser tab; below them is the iDNA version.



The Sidebar Follows the Setup

The sidebar shows only the pages that make sense at the current stage of the setup, and the interface opens on the next page to work on:

Stage	Sidebar shows	Opens with
No license uploaded	[License]	[License]
License uploaded, no User ID	[License], [User ID]	[License]
User ID uploaded, no servers yet	also [Server List] and [Config Manager]	[Config Manager]
Servers in the server list	also the content packages under [Core Config] and [Optional Config]	[Server List]

First Setup at a Glance

1. Upload the license (see [License](#)).
2. Upload the Notes ID that iDNA uses for the collection (see [User ID](#)).
3. Run the Config Manager: discover the servers in each Domino domain, choose the address book servers and the servers to analyze, then click [Apply Settings] (see [Config Manager](#)).
4. Check that iDNA can access every server and fix missing access rights (see [Server List](#)).
5. Set up the optional content packages you need, for example Domino Event Log or Mail Routing Activity (see [Content Packages](#)).

License

The page shows whether your license is valid and until when ([Valid thru]). If servers in your server list are not covered by the license, they are listed as [Unlicensed servers].

To upload a new license file:

1. Select [I have read and agree to the General Terms and Conditions].
2. Choose the license file at [Upload new license file].
3. Click [Upload].

After a successful upload, [Continue to User ID] takes you to the next page.

User ID

iDNA reads the Domino Directory, the server databases and the usage data with a Notes ID that you provide. The ID needs access to all servers in scope; see [System Requirements, Access and Permissions](#).

The page shows the ID in use ([Current ID]) and when it was uploaded ([Uploaded]). To upload an ID:

1. Click [Browse...] and select the ID file.
2. Enter the ID's password in [Password].
3. Click [Upload].

After a successful upload, [Continue to Server Discovery] takes you to the Config Manager.

Config Manager

The Config Manager sets up the data collection for one or more Domino domains: it finds the servers of a domain, lets you choose the server whose Domino Directory iDNA reads and the servers iDNA analyzes, and writes these selections to the content packages under [Core Config]:

Wizard step	Content packages it sets
2: Address Book Servers	Domino Directory
3: Application/Mail Servers	Server Basics, Database Catalog, Notes Client Activity, Web User Activity (Web User Activity only for servers whose domlog iDNA can access)

The content packages under [Optional Config] are not changed.

Move between steps with [Next] and [Back], or click a step name at the top of the Config Manager. Nothing is saved until you click [Apply Settings] in step 4. Your selections are kept while you move between steps, but they are discarded if you leave the Config Manager without applying them.

Step 1: Server Discovery

Discovery finds the servers of a Domino domain and adds them to the server list.

1. Enter the host name or IP address of one server of the domain in [Entry server host name/IP]. An administration or hub server is recommended.
2. Click [Start Discovery].

iDNA connects to the entry server with the User ID, reads the server documents in its Domino Directory, checks its access to each server it found and adds them to the server list. The progress is shown in the log below the field; until discovery has finished, you cannot leave the step. When the message "Discovery finished." appears, continue with [Next].

Config Manager

1

2

3

4

Server Discovery
Address Book Servers
Application/Mail Servers
Review

Discover Domino servers in your environment by connecting to a single server per domain as the entry point (recommended: an Administration or Hub server). You can repeat this process to discover servers in additional domains.

Entry server host name/IP

- For several domains, run discovery once per domain, each time with an entry server of that domain.
- If your servers are already in the server list, you can skip discovery and click [Next].
- Servers that are not in the Domino Directory of the entry server can be added on the server list (see [Server List](#)).

Step 2: Address Book Servers

Select one server per domain whose Domino Directory iDNA analyzes; users, groups and mail-in databases are collected from this server. Select several servers of a domain only if they hold different address books.

Both this step and the next use two lists:

- [Available Servers] lists the servers of the server list that are not selected, [Active Servers] the selected ones. Move servers with the arrow buttons between the lists or by double-clicking them. [Add all] adds every server the left list shows; [Remove all] clears the selection.
- The filter fields above the lists narrow them by server name. [Only show accessible servers] hides the servers iDNA cannot access; these are marked with in red.
- [Copy settings from another content package]: choose a content package as [Source] and click [Copy Settings] to take over its server selection.

When you open the step, [Active Servers] already holds the servers currently configured for Domino Directory.

Config Manager

✓

2

3

4

Server DiscoveryAddress Book ServersApplication/Mail ServersReview

Select a single server per domain for Domino Directory analysis. Users, groups, and Mail-In databases are collected from this server. Only select multiple servers if they hold different address books.

▸ [Copy settings from another content package](#)

Available Servers (30)

Active Servers (1)

Filter available servers

△ app0007/acme

△ app0008/acme

△ app0009/acme

△ app0011/acme

△ app0012/acme

△ app0013/acme

△ app0014/acme

☐ Only show accessible servers

Filter active servers

app0016/acme

← Remove all

Add all →

Back

Next

Step 3: Application/Mail Servers

Select all servers iDNA should analyze. From these servers, iDNA collects basic server information, the database inventory and the Notes usage. Web usage is collected only from servers whose domlog iDNA can access; for the others, Web User Activity is not set.

When you open the step, [Active Servers] already holds the servers currently configured for these content packages.

Config Manager

✓

✓

3

4

Server DiscoveryAddress Book ServersApplication/Mail ServersReview

Select all servers that iDNA should analyze. iDNA collects basic server information, database inventory and Notes usage from these servers. Web usage collection will only be enabled if Domlog is accessible, disabled if it's not.

▸ [Copy settings from another content package](#)

Available Servers (15)

Active Servers (16)

Filter available servers

△ app0007/acme

△ app0008/acme

△ app0009/acme

△ app0011/acme

△ app0012/acme

△ app0013/acme

△ app0014/acme

☐ Only show accessible servers

Filter active servers

app0016/acme

app0017/acme

app0019/acme

app0026/acme

app0027/acme

app0029/acme

app0030/acme

Add all →

← Remove all

Back

Next

Step 4: Review

The last step summarizes what will be applied:

- [Address Book Servers] and [Application/Mail Servers]: the selected servers and the content packages they are applied to.
- [Removed from Collection]: servers that are configured today but no longer selected, and the content packages that will stop collecting from them.
- [Not modified]: the content packages under [Optional Config], which the Config Manager leaves unchanged.

Click [Apply Settings] to save. The button then reads "Settings applied successfully".

5

Config Manager



Review your selections before applying them to the configuration.

⚠ Applying this setup overwrites existing settings. The **Core Config** items below will be replaced with the selections made in the previous steps. Your **Optional Config** is not changed.

If you removed a previously selected server, its existing data is kept — but collection stops for that server, and its information may no longer be visible in iDNA.

Address Book Servers

SELECTED SERVERS

app0016/acme

APPLIED TO

Domino Directory

Application/Mail Servers

SELECTED SERVERS

app0016/acme, app0017/acme, app0019/acme, app0026/acme, app0027/acme, app0029/acme, app0030/acme, app0035/acme, app0036/acme, mail0003/acme, mail0010/acme, mail0020/acme, mail0028/acme, mail0031/acme, mail0032/acme, mail0033/acme

APPLIED TO

Server Basics

Database Catalog

Notes Client Activity

Web User Activity

Removed from Collection

No servers are removed from collection by these selections.

Not modified

These Optional Config items are left unchanged by the Config Manager and can be configured manually.

Domino Event Log

Mail Routing Activity

HCL DLAU

MarvelClient Analyze

Back

Apply Settings

What applying does:

- The content packages under [Core Config] are replaced with your selections.
- Servers that were already configured for a content package keep their settings there, for example a Web User Activity source set up by hand. Newly selected servers get the default settings.
- For a server you removed, collection stops. The data collected so far is kept, but it may no longer be visible in iDNA.

⚠ One selection for four content packages

Step 3 applies the same servers to Server Basics, Database Catalog, Notes Client Activity and Web User Activity. If you configured these content packages for different servers by hand, applying the Config Manager aligns them. Check [Removed from Collection] before you click [Apply Settings], and adjust individual content packages afterwards under [Core Config] if needed.

Adding Another Domain

1. Open [Config Manager] and run discovery with an entry server of the new domain.
2. In step 2, add the address book server of the new domain to the servers already selected.
3. In step 3, add the servers of the new domain.
4. In step 4, check that [Removed from Collection] lists no server you want to keep, and click [Apply Settings].

Server List

The server list shows every Domino server iDNA knows about, whether found by discovery or added manually. For each server, it shows whether iDNA can access it with the User ID:

- [Access]: the server itself.
- [Nab], [Log], [Catalog], [Stats], [Domlog], [Console]: the Domino Directory, log database, catalog, statistics, domlog and server console. These columns are filled in only if the server itself is accessible.

means iDNA can access it. means it cannot; hover over the to see the status code. Fix missing access before you rely on the collected data.

[Manually add a server](#)

Filter

Check Server Access


Total shown: 10

Domino Name ▲	Hostname	Access	Nab	Log	Catalog	Stats	Domlog	Console	Actions
mail0002/acme	mail0002.acme.com	✗							Delete
mail0003/acme	mail0003.acme.com	✓	✓	✓	✓	✓	✗	✓	Delete
mail0005/acme	mail0005.acme.com	✗							Delete
mail0010/acme	mail0010.acme.com	✓	✓	✓	✓	✓	✓	✓	Delete
mail0020/acme	mail0020.acme.local	✓	✓	✓	✓	✓	✗	✓	Delete
mail0028/acme	mail0028.acme.com	✓	✓	✓	✓	✓	✓	✓	Delete
mail0031/acme	mail0031.acme.com	✓	✓	✗	✗	✓	✓	✓	Delete

- [Filter] narrows the list by server name or host name. Click [Domino Name], [Hostname] or [Access] to sort.
- [Manually add a server]: enter the server's host name and click [Add]. Use this for servers that discovery does not find.
- [Delete] removes a server from the list after a confirmation, for example a decommissioned server that is still in the Domino Directory.
- [Check Server Access] opens the access check in the system pages in a new browser tab. There you repeat the access check after fixing access rights, and run the extended check of the server configuration (see [Content Packages - Basic Configuration](#), [Check Server Access](#)).

Content Packages

Content packages define what iDNA collects and from which servers. The sidebar lists them in two groups: [Core Config], the content packages the Config Manager sets, and [Optional Config]. The number next to each content package is the number of servers it is configured for. Only the content packages your license includes are listed.



Content package	Group	Collects	Settings besides the servers
Domino Directory	Core	People, groups and mail-in databases from the Domino Directory	[Type]: [All NABs (incl. Directory Assistance)] (default) or [List of Databases (Comma Separated)] with the database names in [Databases]
Server Basics	Core	Server documents, INI settings, connection documents and statistics	none
Database Catalog	Core	The Notes applications from the server catalog	none
Notes Client Activity	Core	Notes client session activity and usage	none
Web User Activity	Core	HTTP/web user activity, from the Notes domlog or an HTTP resolver	[Type]: [Notes Domlog Database] (default), [HTTP Resolver with Basic Authentication] or [HTTP Resolver with Form Authentication], with the resolver's connection fields

Domino Event Log	Optional	Event and security log data from the Domino log database	none
Mail Routing Activity	Optional	Mail routing events and delivery activity	none
Mail Journal Activity	Optional	Mail activity from a mail journal	[Database Path] (default mailjrn.nsf)
HCL DLAU	Optional	Domino License Analysis (DLAU) usage data	[Database Path] (default d lau . nsf)
MarvelClient Analyze	Optional	Client analytics from the MarvelClient Analyze database	[Database Path] (default panagenda/mc_analyze . nsf)
Message Trace	Optional	Office 365 message trace data	[Username] and [Password]

Click a content package in the sidebar to open it. The page shows its description, the same server lists as the Config Manager (including [Copy settings from another content package]) and its settings. Settings that apply per server, such as [Database Path] or the Web User Activity [Type], belong to the server selected in [Active Servers]: select a server to see or change its values. A required field that is empty is marked red, and [Save] stays disabled until it is filled. [Cancel] discards your changes; Message Trace also has [Reset Configuration], which removes its configuration.

For Web User Activity with an HTTP resolver, the page asks for [Scheme], [Port], [File Path], [Username], [Password] and [Log Fields]; with form authentication also for [Action URL], [Username Field] and [Password Field].

The content packages under [Core Config] are usually set by the Config Manager. Open them directly for settings per server, such as a Web User Activity source, or to change a single content package without running the wizard.

What Changed for Existing Installations

- The admin interface moved from `/idna/cfgc` to `/idna/config`. The old address redirects; update your bookmarks.
- Server discovery is now step 1 of the Config Manager, and the Config Manager sets the Core Config content packages in one go instead of one content package at a time.
- Your existing configuration is kept. Some content packages have new names:

Name before 3.5.0	Name from 3.5.0
Directory/NAB Content	Domino Directory
Domino Server Basics	Server Basics
Session Activity	Notes Client Activity
Domino Web Log	Web User Activity
Domino Log	Domino Event Log

Related Topics

- [Installing iDNA Applications on Linux](#): from a prepared Linux host to the first login.
- [Upgrading iDNA Applications](#): upgrading an existing installation to 3.5.0.
- [System Requirements](#): what the User ID and the Domino servers need.
- [Release Notes v3.5.0](#): everything new in iDNA Applications 3.5.0.